What are the health and safety requirements for Site Dumpers ?

Equipment:	Site Dumpers
Necessary CR	N/A
Forms	
Required	FAS Safe Pass (for all construction site work)
operator	CSCS Articulated Dumper Operation Training
training:	CSCS Site Dumper Operation Training
	Site safety rules, site emergency procedures, etc.
Proposed	Off-road Dump trucks (payload greater than 7 tonnes):
Mandatory	Movement alarm and flashing beacon with CCTV or convex mirrors
safety devices:	or a combination of both to allow vision from the drivers seat at all
	points 1 metre high and 1 metre from the machine at each side and
	at rear of the driver
	Dumpers front tip (no cab) : Reversing Alarm, Flashing Beacon
	Dumpers front tip (with cab): CCTV cameras, Convex mirrors,
	Flashing beacon, Reversing alarm
Other	Pedestrians should be kept out of the working area of dumpers as
precautions:	much as possible
	Steps and handrails should be provided and maintained to ensure
	safe access and egress
	• Vehicles should be fitted with devices to prevent tipping bodies
	collapsing from the raised position during maintenance
	Roads and traffic routes must be level and well maintained
	One way systems should be put in place where practical
	• Wheel stops and other suitable protection must be put in place for
	dumpers tipping over an edge or excavation, etc.
	Ground conditions should be fully assessed before dumping
	For articulated vehicles, the vehicle should be fully aligned
	before tipping occurs
	• Tipping on slopes should be avoided but if it must occur it should
	be carried out with the tipping body raised in the opposite
	direction to the slope.
	Seatbelts should be in good condition and worn at all times
	Appropriate PPE should be given to the driver
	Drivers' cabins should be suitable to protect from adverse
	weather conditions
	Cabs should be fitted with Roll Over Protection Structures
	(ROPs)
	Cabs should be fitted with Falling Object Protection Structures
	(FOPs) where there is a risk of falling objects
	Brakes should be tested regularly
	 All vehicles should be inspected by the driver at the start of the
	shift
	This list is not exhaustive
	Tives that is feet entirementally