What are the health and safety requirements for Scrapers?

Equipment: Scrapers	
Necessary CR N/A	
Forms IVA	
Forms filled N/A	
out by:	
Filled out N/A	
when:	
Required FAS Safe Pass (for all construction site work)	
operator CSCS tractor/dozer training	
training: Site safety rules, site emergency procedures, et	tc.
Proposed CCTV, Convex mirrors,	
Mandatory Flashing beacon, Reversing alarm	
safety devices:	
• On wheeled machines tyres must be maintain	ned in good
precautions: condition, and correctly inflated	
 Haul roads must be maintained for peak effi 	
When two or more scrapers are working on	the same job, a
distance of at least 25m should be kept betw	een them
Work on steep gradients should be avoided	where possible.
• If steep gradients are unavoidable, scrapers	with minimum
overhead structures should be used; bowls s	hould be carried low
to the ground at all times, and not be overful	ll; turns should be
made uphill where possible; and if turn mus	
should be done gradually with the bowl scra	
• Self propelled scrapers being un-sprung sho	
high speed over uneven surfaces and they sh	
in gear when travelling down hill	7 1
When travelling the bowl should be high en	ough to avoid
collisions with the ground or objects on it	8
 Dumping soil off an embankment or fill is b 	est done in thin
layers as it provides for better compaction a	
surface.	
 It is also important that the edge of the emba 	ankment is kent
higher than the centre to prevent the scraper	-
slope	form shaing off the
 Servicing and repairing scrapers can be part 	icularly hazardous
and proper precautions must be taken in acc	•
manufacturers recommendations. A person	
	suitably competent to
do it should carry out work.	vo#
Appropriate PPE should be given to the driv	
• Drivers cabins should be suitable to protect	torm adverse weather
conditions at all times	
All vehicles should be inspected by the driv	er at the start of the
shift	
This list is not exhaustive	